

FOR WINDOWS 10: Google CHROME Browser

1. [J&M Bluetooth® Blu<>Hub® DONGLE Software Update Model DNG44 --<v05.1.3 – 07-24-2018>](#)
2. Single click on the **"File Above"**.
3. ON bottom selection BAR single click on ^ **"Open"**.
4. Double click on **"dfu-bluhub.exe"**.
5. Single click on **"Extract All"**.
6. Then single click **"Extract"**. (((if destination folder already contains **"C: JM-CorpBluHubSoftUpdateDng44---04-1-2---05-28-2018 (4)"**, single click **"Replace the files in destination"**)))
7. Then Double click on **"dfu-bluhub.exe"**, (If Windows info screen asks permission to RUN single click **"RUN"**).
8. If antivirus info screen asks for your permission also, single click **"RUN this program anyway"**.
9. Single click upper right-hand corner **"Red-X"**
10. Follow instructions on firmware **"Update Tool"**
11. Single click on **"Update"**.
12. Wait and watch program **"Update Progress to 100%"**.
13. Single click on **"Exit"** at which point programming is complete for that specific USB plug.
14. Then unplug USB cable and plug the second USB cable from dongle into the same USB port on the laptop/desktop.
15. Double click on **"dfu-bluhub.exe"**.
16. Single click on **"Extract All"**.
17. Then single click **"Extract"**. (((if destination folder already contains **"C: JM-CorpBluHubSoftUpdateDng44---04-1-2---05-28-2018 (4)"**, single click **"Replace the files in destination"**)))
18. Then Double click on **"dfu-bluhub.exe"**, (If Windows info screen asks permission to RUN single click **"RUN"**).
19. If antivirus info screen asks for your permission also, single click **"RUN this program anyway"**.
20. Single click upper right hand corner **"Red-X"**
21. Follow instructions on firmware **"Update Tool"**
22. Single click on **"Update"**.
23. Wait and watch program **"Update Progress to 100%"**.
24. Single click on **"Exit"** at which point programming is complete for the second specific USB plug.
25. Single click upper right hand corner **"Red-X"**
26. Unplug dongle from computer.
27. Plug BluHub dongle back into the motorcycle and turn ON the ignition.
28. Then FIRST hold down on the passenger's pairing button for about 15 seconds until the passenger's module shuts off, at which time the driver's module will STILL BE in pairing mode.
29. Then turn on the driver's Bluetooth headset, hold down on the multifunction button to put it into pairing mode and after about 4-10 seconds, the dongle and driver's headset should pair together.
30. Then turn the motorcycle ignition to the OFF position and then back to the ON position.
31. Then turn on the passenger's Bluetooth headset, hold down on the multifunction button to put it into pairing mode and after about 4-10 seconds, the dongle and passenger's headset should pair together.

32. Now turn ignition back to the OFF position, then back to the ON position and both driver & passenger Bluetooth headsets should pair automatically to the dongle.
33. Then press the volume UP (+) button on each headset until they are at maximum volume level when paired to the dongle, which will reset the headset volume memory when connected to the dongle.
34. Further volume adjustments can then be made using the handlebar/dash mounted controls on the specific motorcycle audio system you are connected to.