



1747 E 23rd St Tucson AZ 85713 – 1-520-624-7000

www.jmcorp.com ,,,, audio@jmcorp.com



Product Manual

Part# HLHS-6582TW-XRP

**J&M Vented Lower Fairing Kit w/ROKKER 6.58" Speakers
for 2014-2020 Harley StreetGlide/RoadGlide**

Description and Specifications

- **Painted Finish:** Gloss/Vivid Black
- **Installation Method:** Easy Bolt-on to Stock Engine Guard
- **Speaker Size:** 6.58" (in.) Diameter
- **Cone Construction:** Black Glass-Fiber
- **Tweeter:** PEI Dome High-Output
- **Frequency Response:** 35-23kHz
- **Sensitivity:** 91 db
- **Magnet Material:** Lightweight Neodymium
- **Impedance:** 2 Ohms
- **Maximum Power:** 200 Watts
- **RMS Power:** 130 Watts
- **Weather Resistant:** Yes
- **Comparison Rating:** ROKKER speakers provide the most significant increase in volume and overall fidelity compared to stock Harley and/or Fosgate.

J&M's vented lower fairings with ROKKER speakers installed are designed for easy installation on the 2014-2020 Harley StreetGlide or RoadGlide with the factory installed engine guard.

Vent adjustment lever allows for simple adjustment of the vent angle opening on either side.

Included ROKKER XRP series 6.58" speakers are spec'd at 2 ohms impedance and 200 watts maximum input (130w RMS - 91db sensitivity).

Lightweight waterproof one-piece woven-fiber driver cone with super-rigid metal basket design.

High-density lite-weight Neodymium magnet structure, specially coated to maintain flux-strength integrity even at extreme operating temperatures.

Integral high-output PEI dome tweeter with custom J&M grills included.

Plug-n-play speaker wiring harness with factory Harley style connectors also included.

Installation Guide

1. Remove the screws holding the speakers from each lower fairing and set the speakers aside.
2. Using a 1/4 drive ratchet, long extension and 10mm deep magnetic socket, thru the hole in the back of the inside speaker box, remove the bolt holding the front fairing cap and set cap aside.
3. Remove the two nuts holding the u-clamps on the back of each lower fairing.
4. Slide into position the C-clamp on the bottom section of the engine guard.
5. Position the left side lower fairing shell on the engine guard and hand tighten the nuts on the two upper studs.
6. Place the larger cap bolt thru the bottom hole of the lower fairing shell, then thru the C-clamp holes and then hand tighten the nut on the bottom side.
7. Slide the entire lower fairing shell into the proper position and hold in place while tightening the two upper U-clamp nuts and the bottom C-clamp bolt.
8. Repeat these steps for the right-side lower fairing shell
9. Route each speaker wire along the top of the engine guard, into the back side of each speaker enclosure.
10. Position the nut-plate properly into the slot on the inside of each front fairing cap and then slide each cap into position paying attention to the slide in tabs.
11. Insert the fairing cap mounting bolt into the 10mm socket, slide thru the hole in the back of the speaker enclosure, and hand tighten each bolt into the nut plate securing the front caps and then tighten into place.
12. Place the left side speaker into position with the mounting spacer underneath, and connect to the speaker wires.

13. Then mount and tighten the speaker into position using the mounting screws provided.
14. Repeat the process with the right side speaker.
15. If you are connecting both the upper and lower fairing speakers together on the front two channels of a 4-channel amplifier, (or two channel amplifier only) use our in-series wiring harness, J&M part# HLRK-6652-ISCH, so that the final impedance load on the amplifier will not drop below 2-ohms, which can damage your amplifier.

Thank you for the confidence you have shown in J&M Corporation by purchasing one of our innovative products.

If you have any question or comments about this product, you may contact us at USA 1-520-624-7000 Monday thru Friday, 8:30AM thru 4:30PM Mountain Standard Time.

WARRANTY AND REPAIR INFORMATION

TWO YEAR LIMITED WARRANTY In order to facilitate the servicing of this warranty, the Warranty Registration Form should be filled out and returned within 10 days of the date of purchase. However, return of the Warranty Registration Form is not a precondition of this warranty, and this Warranty will be observed by **J&M CORPORATION** whether or not the Warranty Registration Form is returned, on the condition that other satisfactory evidence of the date of the original purchase is provided to **J&M CORPORATION**.

WHO PROVIDES THE WARRANTY? This warranty is provided by **J&M CORPORATION**.

WHO IS PROTECTED? This warranty is extended only to the original owner of this J&M CORPORATION product and may not be transferred or assigned.

WHAT IS COVERED AND HOW LONG? This warranty covers all defects in material or workmanship of our product for a period of 2 years from date of original retail purchase. At its option, **J&M CORPORATION** will repair or replace any defective part(s) or equipment.

The provisions of the warranty shall not apply to any unit which has been subjected to misuse, neglect, incorrect mechanical or electrical installation, unauthorized modifications, accident, nor to units which have been repaired or altered outside of our factory.

PROCEDURE FOR OBTAINING PERFORMANCE OF WARRANTY In the event that the product does not conform to this warranty, the product should be shipped prepaid to the **J&M CORPORATION** service facility. Transportation charges, insurance fees, and labor costs for shipment, removal, or reinstallation of our product are not covered by this warranty. Loss or damage in shipment is the sole responsibility of the freight carrier.

FOR YOUR INFORMATION Repair as provided under this warranty is the exclusive remedy of the consumer. **J&M CORPORATION** shall not be liable for any incidental or consequential damages or for breach of any express or implied warranty on this product. Except to the extent prohibited by applicable law, any implied warranty of merchantability or fitness for a particular purpose on this product is limited in duration to the duration of the warranty. Some states do not allow the exclusion or limitation of incidental or consequential damages, or allow limitations on how long an implied warranty lasts, so the above limitations or exclusion may not apply to you. This warranty gives you specific legal rights which vary from state to state.

J&M CORPORATION reserves the right to make changes in design and to make improvements in its products without the obligation to incorporate the changes or improvements in any of its previously manufactured products.

J&M CORPORATION has not authorized anyone to make representations or warranties other than the warranty contained herein.

The above warranty is effective for all products manufactured after 10/01/86.

NON-WARRANTY REPAIR RATES **J&M CORPORATION** reserves the right to change the labor repair rates without prior notice. At the time of this printing the out-of-warranty repair is \$40 per hour for labor only. However, the customer is advised to verify the current rate when he/she calls customer service to obtain the return authorization number.

FACTORY SERVICE ADDRESS J&M Corporation, 1747 E 23RD ST, Tucson, Arizona, 85713, U.S.A. Tel: 1-520-624-7000 audio@jmc corp.com www.jmc corp.com

CUSTOMER SERVICE NUMBER 1-520-624-7000

Thank you for the confidence you have shown in J&M Corporation by purchasing one of our innovative products.

If you have any question or comments about this product, you may contact us at USA 1-520-624-7000 Monday thru Friday, 8:00AM thru 5:00PM Mountain Standard Time.



1747 E 23RD ST Tucson, AZ
85713 U.S.A.

Tel 1-520-624-7000

Website: <http://www.jmc corp.com>

E-mail: audio@jmc corp.com



WARRANTY REGISTRATION FORM Please fill out this card completely and mail it immediately after purchase. Please be sure that your zip code and serial number (if applicable) are legible. This will help us to serve you better.

(PLEASE PRINT)

Name _____

Address _____

City _____ State _____ Zip _____

Motorcycle Other E-mail _____

Make _____ Model _____ Year _____

Product part number _____

Serial number (if applicable) _____

Date of purchase _____

Name of dealer it was purchased from _____



Mail to:
JM Corporation 1747 E
23RD ST Tucson, AZ
85713
U.S.A.