

ROKKER® XXR

**6.71" Lower Fairing Speaker
Kit for 2014-2020 Harley®
Ultra/Ltd/CVO w/Water
Cooled Reservoir**

#HLRKW-6712TW-XXR

**Installation
and Operation
Instructions**

Product Description

J&M's custom lower-fairing speaker/housing kit has been design for the 2014-2020 Harley Ultra, Ultra Ltd or CVO, with the liquid cooled lower fairing mounted reservoir.

The included 6.71" ROKKER speakers are spec'd at 2 ohms impedance and 350 watts maximum input (200w RMS - 91db sensitivity), they provide the ultimate in raw audio power and include the new custom grills with built-in high-output tweeters.

Featuring a lightweight waterproof one-piece woven-fiber driver cone with super-rigid metal basket design.

High-density lite-weight Neodymium magnet structure, specially coated to maintain flux-strength integrity even at extreme operating temperatures.

High efficiency VENTED voice-coil for improved cooling when operating at high volume levels for extended periods.


Custom speaker grills with high-output tweeters for crystal clear sound at highway speeds.

These are THE most powerful speakers you can buy for your Harley and they will perform extremely well when used with a medium to high-powered accessory amplifier.

These high-impact quality molded speaker housing inserts are textured in a matt finish and can be painted to match the color of your Bagger.

Installation Instructions

1. Remove both ROKKER speakers and grills from the housings using a #2 phillips (**Figure A and B**)
2. Pop out both left and right-side lower fairing inserts from the stock Ultra lower fairings.
3. Remove the 7/16" nut from the inside of each lower housing and then remove the front lower fairing caps on each side.
4. Remove the 3 #T25 Torx screws from the front of each side lower housing, and then remove the inside pod housings from the lower fairing painted shells.
5. Remove the vent knobs from each side of the existing lower housings and reinstall the knobs on each side of the new housings.
6. Drill a 7/16" hole on each lower fairing shell where indicated to allow the wiring harness access to each speaker as you reassemble. (**Figure B**)



7. Install the new left and right-side housings using the provided panhead Philipps screws in place of the Torx screws that were removed.

8. Reinstall each side lower fairing front cap using the previously removed 7/16" nuts.

9. Plug wire spades into each speaker and install them back into the new lower housings, using the long black Philipps pan head screws, making sure that the grill mounted tweeter is facing outward on each side, and the ROKKER logo is not upside down. **(Figure C)**

10. Route the wires from each lower speaker up into the fairing and connect to the audio system.

11. Test each speaker for proper operation before reassembling the fairing.



Thank you for the confidence you have shown by purchasing one of J&M's innovative products. If you have any questions during the installation, or require further assistance, you may call us at 1-800-358-0881 from 8:00 a.m. to 5:00 p.m. Mountain Standard Time, Monday through Friday.



Tucson, Arizona U.S.A.

Tel (800) 358-0881

Website: <http://www.jmcorp.com>

E-mail: audio@jmcorp.com

WARRANTY AND REPAIR INFORMATION

TWO YEAR LIMITED WARRANTY In order to facilitate the servicing of this warranty, the Warranty Registration Form should be filled out and returned within 10 days of the date of purchase. However, return of the Warranty Registration Form is not a precondition of this warranty, and this Warranty will be observed by **J&M CORPORATION** whether or not the Warranty Registration Form is returned, on the condition that other satisfactory evidence of the date of the original purchase is provided to **J&M CORPORATION**.

WHO PROVIDES THE WARRANTY? This warranty is provided by **J&M CORPORATION**.

WHO IS PROTECTED? This warranty is extended only to the original owner of this J&M CORPORATION product and may not be transferred or assigned.

WHAT IS COVERED AND HOW LONG? This warranty covers all defects in material or workmanship of our product for a period of 2 years from date of original retail purchase. At its option, **J&M CORPORATION** will repair or replace any defective part(s) or equipment.

The provisions of the warranty shall not apply to any unit which has been subjected to misuse, neglect, incorrect mechanical or electrical installation, unauthorized modifications, accident, nor to units which have been repaired or altered outside of our factory.

PROCEDURE FOR OBTAINING PERFORMANCE OF WARRANTY In the event that the product does not conform to this warranty, the product should be shipped prepaid to the **J&M CORPORATION** service facility. Transportation charges, insurance fees, and labor costs for shipment, removal, or reinstallation of our product are not covered by this warranty. Loss or damage in shipment is the sole responsibility of the freight carrier.

FOR YOUR INFORMATION Repair as provided under this warranty is the exclusive remedy of the consumer. **J&M CORPORATION** shall not be liable for any incidental or consequential damages or for breach of any express or implied warranty on this product. Except to the extent prohibited by applicable law, any implied warranty of merchantability or fitness for a particular purpose on this product is limited in duration to the duration of the warranty. Some states do not allow the exclusion or limitation of incidental or consequential damages, or allow limitations on how long an implied warranty lasts, so the above limitations or exclusion may not apply to you. This warranty gives you specific legal rights which vary from state to state.

J&M CORPORATION reserves the right to make changes in design and to make improvements in its products without the obligation to incorporate the changes or improvements in any of its previously manufactured products.

J&M CORPORATION has not authorized anyone to make representations or warranties other than the warranty contained herein.

The above warranty is effective for all products manufactured after 10/01/86.

NON-WARRANTY REPAIR RATES **J&M CORPORATION** reserves the right to change the labor repair rates without prior notice. At the time of this printing the out-of-warranty repair is \$40 per hour for labor only. However, the customer is advised to verify the current rate when he/she calls customer service to obtain the return authorization number.

FACTORY SERVICE ADDRESS J&M Corporation, 1415 S. Cherry Avenue, Tucson, Arizona, 85713, U.S.A. Tel: 1-800-358-0881 audio@jmc Corp.com www.jmc Corp.com

CUSTOMER SERVICE NUMBER 1-800-358-0881



WARRANTY REGISTRATION FORM Please fill out this card completely and mail it immediately after purchase. Please be sure that your zip code and serial number (if applicable) are legible. This will help us to serve you better.

(PLEASE PRINT)

Name _____

Address _____

City _____ State _____ Zip _____

Motorcycle Other E-mail _____

Make _____ Model _____ Year _____

Product part number _____

Serial number (if applicable) _____

Date of purchase _____

Name of dealer it was purchased from _____



Mail to:
J&M Corporation
1415 S. Cherry Avenue
Tucson, AZ 85713
U.S.A.